



The vacuum loader is equipped with options.

DISAB Centurion™ LN10

Usage

DISAB Centurion™ LN10 is designed for industrial applications suitable for suctioning both solid and liquid materials. Its strong and efficient suction feature makes it appropriate for industries such as cement, lime, chemicals, plastic, foundries, steelworks, quarries, pulp & paper, shipyards, and energy. The vacuum unit is designed and adapted for mounting onto a four-axle truck chassis with two front axles.

Characteristics

A DISAB Centurion™ LN10 is powered by a separate diesel engine and is equipped with a suction only feature. Its round tank design makes it suitable for handling both wet and dry materials and possess great flexibility for different applications with multiple options available.

The tank is available in 10 / 12 / 14 m³. The discharge of materials occur by tipping the tank and the tank tipping system consists of a hydraulic front cylinder, double acting system to make it easy-to-use for the operator. The tailgate is hydraulically operated and locked.

Benefits

DISAB Centurion™ LN10 offers extremely good suction capacity. The vacuum pump is powered by a separate diesel engine which results in a more quiet operation, as well as allowing operation using tax-free diesel.

Other benefits include:

- The vacloader can operate independently of the truck.
- More options when it comes to choosing a chassis.
- The material tank and filter compartment are combined and the dust from the filter compartment is emptied through a hatch in the partition wall in the tank at the same time as the tank is tilted.
- Sold with extensive DISAB Academy training included to optimize safety and economical value
- Multiple options available, tailored to your specific needs.
- Operated using a hand held radio for an optimized ergonomical experience for the operator.

Technical Data Chart for DISAB Centurion™ LN10

Description

Vacuum pump	Three-Lobe Roots Pump	Max vacuum, mbar	950
Max overpressure, mbar	N/A	Air volume m ³ /h (unloaded)	8,100
Operating speed (rpm)	2,650	Power, kW	220
Voltage Frequency, V/Hz	N/A	Power source	Diesel
Engine type	Stage III / Stage V	Tank material	Carbon steel / stainless steel
Tank volume (m ³)*	10 / 12 / 14	Total tank volume (m ³)	12.7 / 14.7 / 16.7
Tank tipping system	Hydraulic front cylinder, double acting system. Tailgate is hydraulically operated and locked.	Main filter system (m ²)	70 galvanized / stainless steel cages with filter socks in needled polyester glazed surface. Filter area is 26 m ² .
Cooling air filter	Cartridge filter	Safety filter surface (m ²)	33
ATEX approved	N/A		

* Excluding filter volume

Core function

Suction	Yes
Blow / ejec	N/A
Transport (ADR)	N/A
Discharge	By tipping the tank
Dry materials	Yes
Wet materials	Yes

Weight and Dimensions**

Complete unit including chassis (kg)	23,400
Total unit length including truck chassis (mm)	10,500
Total width (mm)	2,500
Height with hose boom (mm)	4,000

** Weight and dimensions are approximate and dependant of chassis and the vacuum unit equipment.



The DISAB Centurion™ LN10 mainly consists of a permanently mounted engine room with a vacuum pump that is powered by a separate diesel engine and a tiltable vacuum/pressure tank for material handling.

DISAB Centurion™ LN10 is a truck mounted unit that can transport bulk materials and liquids by vacuum or overpressure through a hose system with a diameter up to 200 mm.